

Specifications	6 3 ' +	6 3 ' + 7	6 3 + 6
Work plate dimension	3135mm(5 inch)	3135mm(5 inch)	3135mm(5 inch)
Work plate material	stainless steel cover with ceramic	stainless steel cover with ceramic	stainless steel cover with ceramic
Motor type	Brushless DC motor	Brushless DC motor	Brushless DC motor
Motor rating input	18W	18W	18W
Motor rating output	10W	10W	10W
Power	550W	550W	530W
Heating output	500W	500W	500W
Voltage	100-120/200-240V 50/60Hz	100-120/200-240V 50/60Hz	100-120/200-240V 50/60Hz
Stirring positions	1	1	1
Max. stirring quantity[H ₂ O]	20L	20L	20L
Max. magnetic bar[length]	80mm	80mm	80mm
Speed range	100-1500rpm resolution-1rpm	100-1500rpm resolution-1rpm	0-1500rpm resolution-1rpm
Speed display	LCD	LCD	Scale
Temperature display	LCD	LCD	Scale
Heating temperature range	Room temp.-340°C, increment 1°C	Room temp.-340°C, increment 1°C	Room temp.-340°C
Temperature control accuracy	-1°C(<100°C) -1%(>100°C)	-1°C(<100°C) -1%(>100°C)	-
Over temperature protection	420°C	420°C	420°C
Temperature display accuracy	-0.1°C	-0.1°C	-0.5°C
External temperature sensor	PT1000 (accuracy -0.2)	PT1000 (accuracy -0.2)	-
"Hot" warning	50°C	50°C	-
Timer function	-	1min to 99h 59min	-
Data connector	RS232	RS232	-
Protection class	IP42	IP42	IP42
Dimension[WxDxH]	160x280x85mm	160x280x85mm	160x280x85mm
Weight	2.8kg	2.8kg	2.8kg
Permissible ambient temperature and humidity	5-40°C, 80%RH	5-40°C, 80%RH	5-40°C, 80%RH